



PISCEAN CENTURY CHEMICALS PTE LTD

Head Quarters : Singapore
No. 13 Tuas Link 1 Singapore 638589 Tel : (65) 6862 6028 (6 Lines) Fax : (65) 6862 6018
Website : www.pisceanchemicals.com
E-mail : piscean@pacific.net.sg / admin@pisceanchemicals.com

CELLUFIX CF600/ 10-2007

CELLUFIX CF600

CELLUFIX CF600 is a cationic fixing agent for use on pigment dyeing on cotton and other cellulosic garments. It is used to improve wet fastnesses on cellulosic fibres that are dyed with Reactive, pigment, sulphur and direct dyes.

CELLUFIX CF600 contains cationic water dispersible soft resin and surfactants with high affinity and exhaustion to cellulosic fibres in water medium.

CELLUFIX CF600 does not contain NP, APEO and banned amines.

PHYSICAL PROPERTIES:

Appearance	:	Yellowish transparent to light brown transparent solution
pH 1% solution	:	5.0 ± 1.0
Ionic Nature	:	Cationic
Odour	:	Slight
Diluent	:	Water
Solubility	:	Dispersible in water

USER'S RECOMMENDATION:

(For pigment dyeing, as cationising agent)

- Load Garments with Liquor ratio of between 1:10 ~ 1:15.
- Dose between 2 ~ 4% o.w.g of **CELLUFIX CF600** while machine is running.
- Run garments with **CELLUFIX CF600** at 35°C for 5 minutes.
- Add 4% o.w.g of Pigitex 45, run 15~20 mins.
(For Dark Shades, addition of 1~2g/L of Soda Ash is necessary)
- Rinse 2 x cold.
Add Pigidyes slowly into running machine; raise temperature of bath to 50~60°C.
Run for 15 to 25 mins till dye bath is exhausted.
- Continue with cellulase treatment or softening.

PACKING:

120kg in Plastic Drum, metal ring frame with pin-lock.

STORAGE:

To store cool under shade to prolong shelf life of product.

Keep lid tight when not in use to prevent possible contamination to the product.

TRANSPORT:

Product is not classified as hazardous for transport.

Separate MSDS is available upon request

百
胜
世
纪
化
工
私
人
有
限
公
司



CERT. NO. : 2001-2-1286
SS ISO 9001: 2000



CERT. NO : SG-1286



MEMBER OF
SINGAPORE BUSINESS
FEDERATION