



# PISCEAN CENTURY CHEMICALS PTE LTD

Head Quarters : Singapore  
No. 13 Tuas Link 1 Singapore 638589 Tel : (65) 6862 6028 (6 Lines) Fax : (65) 6862 6018  
Website : [www.pisceanchemicals.com](http://www.pisceanchemicals.com)  
E-mail : [piscean@pacific.net.sg](mailto:piscean@pacific.net.sg) / [admin@pisceanchemicals.com](mailto:admin@pisceanchemicals.com)

CELLUFIX CF750

## CELLUFIX CF750

**CELLUFIX CF750** is a strong cationic fixing agent for the after treatment of reactive dyeing on 100% cotton and other cellulosic blended materials. It is widely used for improving wet fastness and other fastness properties on cellulosic fibres that are dyed with Reactive and / or Direct dyes.

**CELLUFIX CF750** is also suitable to be used as a fixing agent in the pigment garment dyeing process.

### PHYSICAL PROPERTIES:

Appearance	:	Viscous colorless to slightly yellowish solution
pH at 1g/L	:	5.5 ± 0.5
Ionicity	:	Cationic
Odour	:	Negligible
Diluent	:	Suitable treated clean water

### USER'S RECOMMENDATION:

As dye fixatives	:	Use up to 2% - 4% on W.O.F.
Temperature	:	40°C - 60°C
pH of bath	:	4.5 - 6.0
Time	:	20 - 40 minutes

### PACKING:

120kg in HDPE Drum, metal ring frame with pin-lock.

### STORAGE:

To store cool under shade to prolong shelf life of product.  
Keep lid tight when not in use to prevent possible contamination to the product.  
Stir product well before application.

### TRANSPORT:

Product is non-flammable by itself and is not classified as hazardous for transport.

*Separate MSDS is available upon request.*

百  
胜  
世  
纪  
化  
工  
私  
人  
有  
限  
公  
司



CERT. NO. : 2001-2-1286  
SS ISO 9001: 2000



CERT. NO : SG-1286



MEMBER OF  
SINGAPORE BUSINESS  
FEDERATION

Page 1 of 1

**CHINA : PISCEAN CHEMICALS (SUZHOU) PTE LTD**  
No. 9, Xie Tang District, Suzhou Industrial Park, Suzhou, Jiang Su Province, China 215123.  
Tel / 电话 : (86) 512-6547 2722 / 6547 3799 / 6593 3037 Fax / 传真: (86) 512-6547 0988  
中国江苏省苏州市 215123, 苏州公业区斜塘分区 9 号

*Piscean Century Chemicals Pte Ltd does not take liability to the effectiveness of the products since users application conditions may be different.*